

SYDNEY

25 – 27 Green St
East Botany, NSW 2019
Ph: +61 2 9666 3788
Fax: +61 2 9666 4805

MELBOURNE

29 Trade Place
Vermont, VIC 3133
Ph: 03 9872 4033
Fax: 03 9872 4099

BRISBANE

Unit 6/5 Deakin Street
Brendale, QLD 4500
Ph: 07 3205 8510
Fax: 07 3205 9616

SINGAPORE

H.K. Moey
9 Elias Terrace
Singapore 519772
Ph: +65 6582 8103
Fax: +65 6584 8100
Mobile: +65 9751 0026



TECHNICAL DATA

Eraspray Gun Solvent

SPRAY GUN AND MIXING HEAD CLEANING SOLVENT

Era Spray Gun Solvent is a unique solvent for use in the polyurethane industry. It is designed for soaking spray guns, mixing heads and other equipment to facilitate removal of cured polyurethane and polyureas.

Place used spraying or mixing equipment in Era Spray Gun Solvent and allow to soak overnight. Overnight soaking should dissolve the cured elastomer or at least soften the elastomer to the point where it can be air-blown or wire brushed away.

PRODUCT SPECIFICATION

Appearance	Clear liquid
Boiling point	Not determined
Specific gravity	Not determined
Odour	Slight amine like
Flash point	Not determined
Solubility	Miscible

HANDLING

This material contains hazardous components. It is strongly recommended that the user reads, understands and follows instructions set out in the Material Safety Data Sheets before use.

1. Avoid inhalation of fumes. In case of inhalation, refer to MSDS and seek medical assistance.
2. Avoid contact with skin. In case of contact with skin, wash thoroughly with soap and water. Components of this product can be absorbed through the skin with toxic effects.
3. Wear gloves, eye protection and splash suit or apron.
4. Maintain adequate ventilation at all times.

This information is of general nature and is supplied without recommendation of guarantee. It does not make claim to be free from patent infringement. Properties shown are typical and do not imply specification tolerances. Era Polymers cannot accept liability for loss or damage through use. Whilst these technical details are based on expert knowledge, practical experience and laboratory testing, successful application depends upon the nature and conditions in which the products are supplied. Users must, by comprehensive testing, evaluate this product in their own application.

