



ERA Polymers Pty.  
Ltd.

A.B.N. 14 003 055 936  
25-27 Green St  
Banksmeadow  
NSW 2019

## TECHNICAL DATA

## ERACOAT FCA

*Accelerator*

ERACOAT FCA Accelerator is an additive which accelerates the curing rate of ERACOAT FC 2450 coating. ERACOAT FCA Accelerator is used to reduce the tack-free time of ERACOAT FC 2450 coating. It also reduces the recoating time as it initiates a faster curing of ERACOAT FC 2450 coating.

### Uses

Interior timber flooring, particleboard and cork flooring  
*Not suitable for external application or wet areas*

**Storage** – Keep away from direct sunlight and Extreme temperature. Store between 5°C and 30°C

**Note:** All solvent-based coatings can contribute to yellowing of certain types of water based house paints. Ensure walls and callings have completely dried before coating the floor. This coating is NOT suitable for external application or wet areas

### Properties

|                        |                       |                           |           |
|------------------------|-----------------------|---------------------------|-----------|
| <b>Appearance</b>      | Clear coloured liquid | <b>Recoat</b>             | 3 - 5Hr*  |
| <b>Viscosity (cps)</b> | 25cPs ± 30cPs         | <b>Self Life</b>          | 12 months |
| <b>Mixing Ratio</b>    | 5 – 10ml/L            | <b>Sanding Properties</b> | Excellent |

\*Depending on weather conditions

### Directions for use

- Add ERACOAT FCA Accelerator to ERACOAT FC 2450 coatings at a ratio of 5-10% by volume
- Stir thoroughly
- Apply the coating as per direction on the product label and data sheet.

This information is of general nature and is supplied without recommendation of guarantee. It does not make claim to be free from patent infringement. Properties shown are typical and do not imply specification tolerances. Era Polymers cannot accept liability for loss or damage through use. Whilst these technical details are based on expert knowledge, practical experience and laboratory testing, successful application depends upon the nature and conditions in which the products are supplied. Users must, by comprehensive testing, evaluate this product in their own application.

Version: 1

Date of Issue: 11/12/2008

Page 1 of 2

ERACOAT FCA  
(Accelerator)





**ERA Polymers Pty.  
Ltd.**

A.B.N. 14 003 055 936  
25-27 Green St  
Banksmeadow  
NSW 2019

### Maintenance of the finished floor

- Avoid dragging furniture over newly coated floor
- Use protective pads on the bottom of all furniture legs
- Gently remove dirt, sand and grit from the surface to minimise scratching and damaging the floor surface

**Avoid stiletto heels at all times**

### Health and safety

- ERACOAT FCA Accelerator contains solvents care should be exercised when handling.
- Use only in well ventilated areas.
- Avoid breathing vapours.
- Wear Appropriate PPE before spraying

**Please read ERACOAT FCA Accelerator MSDS before using this product**

This information is of general nature and is supplied without recommendation of guarantee. It does not make claim to be free from patent infringement. Properties shown are typical and do not imply specification tolerances. Era Polymers cannot accept liability for loss or damage through use. Whilst these technical details are based on expert knowledge, practical experience and laboratory testing, successful application depends upon the nature and conditions in which the products are supplied. Users must, by comprehensive testing, evaluate this product in their own application.

Version: 1

Date of Issue: 11/12/2008

Page 2 of 2

**ERACOAT FCA  
(Accelerator)**