



ERA Polymers Pty.
Ltd.
A.B.N. 14 003 055 936
25-27 Green St
Banksmeadow
NSW 2019

TECHNICAL DATA

RACOAT FCA

Wet Edge

ERACOAT FCA Wet Edge is a blend of additives that slows solvent evaporation and increases working time of ERACOAT FC coatings. This product is for interior use only.

Uses

Interior timber flooring, particleboard and cork flooring
Not suitable for external application or wet areas

Storage – Keep away from direct sunlight and Extreme temperature. Store between 5°C and 30°C

Note: All solvent-based coatings can contribute to yellowing of certain types of water based house paints. Ensure walls and callings have completely dried before coating the floor. This coating is NOT suitable for external application or wet areas

Properties			
Appearance	Clear coloured liquid	Recoat of coating	12Hr*
Viscosity (cps)	25cPs ± 30cPs	Self Life	12 months
Mixing Ratio	5 – 10ml/L	Sanding Properties	Excellent

*Depending on weather conditions

Directions for use

- Add ERACOAT FCA Wet Edge to ERACOAT FC 2450 coatings at a ratio of 5-10% by volume
- Stir thoroughly
- Apply the coating as per direction on the product label and data sheet.

This information is of general nature and is supplied without recommendation of guarantee. It does not make claim to be free from patent infringement. Properties shown are typical and do not imply specification tolerances. Era Polymers cannot accept liability for loss or damage through use. Whilst these technical details are based on expert knowledge, practical experience and laboratory testing, successful application depends upon the nature and conditions in which the products are supplied. Users must, by comprehensive testing, evaluate this product in their own application.

Version: 1

Date of Issue: 11/12/2008

Page 1 of 2
ERACOAT FCA
Wet Edge





**ERA Polymers Pty.
Ltd.**

A.B.N. 14 003 055 936
25-27 Green St
Banksmeadow
NSW 2019

Maintenance of the finished floor

- Avoid dragging furniture over newly coated floor
- Use protective pads on the bottom of all furniture legs
- Gently remove dirt, sand and grit from the surface to minimise scratching and damaging the floor surface

Avoid stiletto heels at all times

Health and safety

- ERACOAT FCA Wet Edge contains solvents care should be exercised when handling.
- Use only in well ventilated areas.
- Avoid breathing vapours.
- Wear Appropriate PPE before spraying

Please read ERACOAT FCA Wet Edge MSDS before using this product

This information is of general nature and is supplied without recommendation of guarantee. It does not make claim to be free from patent infringement. Properties shown are typical and do not imply specification tolerances. Era Polymers cannot accept liability for loss or damage through use. Whilst these technical details are based on expert knowledge, practical experience and laboratory testing, successful application depends upon the nature and conditions in which the products are supplied. Users must, by comprehensive testing, evaluate this product in their own application.

Version: 1

Date of Issue: 11/12/2008

Page 2 of 2
ERACOAT FCA
Wet Edge